



KEY FEATURES

IP23

Enclosure Range

- ▶ Made to Energy NSW Specifications
- ▶ Suitable for Single Phase & Three Phase Applications
- ▶ IP23 Rated Meter Enclosure
- ▶ Cable Management Tie off Point and Lead Entry Protection AS/NZS 3000:2018
- ▶ 570 X 560 X 6mm Pre-drilled Double Hinged Meter Panel
- ▶ Door Open Strap for Easy Installation and Maintenance
- ▶ Safe 4X Ingress Protection Flanges Rear of Panel
- ▶ Panel Support Ramp for Installation Ease and Panel Sag Prevention
- ▶ 75mm Behind Meter Panel
- ▶ Knockouts Rear and Base for Convenient Cable Access
- ▶ Available with 12 or 18 Pole Surface Mount Din Rail Enclosure
- ▶ Grey RAL 7035 Powder Coat
- ▶ Wrinkle Finish Hides Brush Strokes if repainted
- ▶ Suitable as Construction Site Switchboard with Regulated Safety Features

Technical Specifications

Specifications	Width	Height	Depth
MAU60P	600 mm	600 mm	250 mm
Meter Panel	570 mm	560 mm	6 mm

Product	Order Code	Meter Isolator	Quantity
600mm x 600mm x 250mm Single Two Meter	MAU 60P	▶ 600mm x 600mm x 250mm Single Two Meter	24
			1

Available Accessories

Code	Occupancy	Width (mm)	Height (mm)	Depth (mm)	Quantity
PME12	▶ 12 Pole Surface Mount Din Rail Enclosure	160	260	60	10
PME18	▶ 18 Pole Surface Mount Din Rail Enclosure	160	365	60	10