



KEY FEATURES

- ▶ SA Power Network Approved
- ▶ Designed to meet AS3000 Standard
- ▶ IP23 Protection Rating
- ▶ Dedicated DIN for 1 x 3 Phase Panel Isolator
- ▶ Dedicated DIN for 1 x 3 Phase Panel Isolator & Lock-off
- ▶ Provision of Panel for additional 3 Phase Lock-Off's Allow for up to 4 x Multi Phase Meters
- ▶ Pre-wired available using Australian Made Flex Cable Complete with Insulated end Terminals
- ▶ 150mm Depth Behind Panel as required for Multiple Tenancy Application
- ▶ Plinth, Rain Hood and flush mount available

IP23

Enclosure Range

Technical Specifications

Specifications	Width	Height	Depth
Size	700	1125	325
Panel	550	825	6
Neutral Grid	2 x Ø5mm (Suits up to 10mm) 10 x Ø8mm (Suits up to 25mm)		
Earth Grid	2 x Ø5mm (Suits up to 10mm) 10 x Ø8mm (Suits up to 25mm)		
Mains Neutral	1 x Ø5.5mm; 1 x Ø7mm; 2 x Ø9mm; 1 x 9mm x 9mm (Suits 75mm)		

Order Code	Name	Meter Isolator	Order Code	Panel Isolator	Quantity
MES6	Standard	(N)	24-Pole	(N)	1
MES6-MI	Standard MI	6 x 1 Phase 63A 6kA	24-Pole	1 x 3 Phase 63A 6kA	1
MES6-P75H	Plinth/ Hood Mounted	6 x 1 Phase 63A 6kA	24-Pole	1 x 3 Phase 63A 6kA	1

Available Accessories

Order Code	Name	Description	Quantity
PLS4-75	SA Type 4 Plinth (Suits SA Type 6)	▶ SA Type 4 Plinth 3mm Steel 750(H) 700(W) 325(D)	1
DRS6L	Door - with Lock	▶ STD SA Type 6 Replacement Hinged Door	1
DRL-G	Door Lock	▶ Keyed to SPAN & ETSA Standard	1
MPS6-6D	Spare Part-SA Type 6/6 Meter Panel	▶ SA Type 6 Hinged Meter Panel Drilled for 6 Units	1
MPS6-B	Spare Part-SA Type 6 Blank Meter Panel	▶ Hinged Meter Panel Blank for Custom Projects	1